

The principles of this invention having been fully explained in connection with the foregoing, I hereby claim as my invention:

1. A fishing rod handle which comprises
a handle member, said handle member having an internal
5 hollow and an external surface,
a fishing rod blank, a portion of said fishing rod blank
being insertable within said handle member hollow, and
a plurality of vibration disks, each said disk being
attachable to that portion of the fishing rod blank that is inserted within said
10 hollow handle member,
wherein vibrations emanating from the rod blank are
transferred through the vibration disks and through the handle member to
the external surface of the handle member.
2. The fishing rod handle of claim 1 wherein the internal
15 hollow of the handle member comprises a linear aperture defined within the
handle member.
3. The fishing rod handle of claim 2 wherein the linear
aperture has an internal cylindrical wall and the external surface of the
handle member is parallel linear with that cylindrical wall.

4. The fishing rod handle of claim 1 wherein the handle member hollow has a first open end and a second closed end, and including a nose cone, said nose cone having an axially disposed aperture for receiving a portion of the rod blank therewithin and said nose cone
5 being insertable within the first open end of the handle member hollow.

5. The fishing rod handle of claim 1 wherein each vibration disk comprises a flat circular disk member having a central aperture for receiving a portion of the rod blank therewithin.

6. The fishing rod handle of claim 5 wherein each vibration
10 disk further includes a plurality of prongs extending outwardly from the flat disk member.

7. The fishing rod handle of claim 6 wherein each vibration disk has a first disk face and each of the plurality of outwardly extending prongs is bent toward the first disk face.

8. The fishing rod handle of claim 7 wherein the vibration
15 disks that are attached to the disk blank are attached such that the prongs of each disk are bent in the same direction.

9. The fishing rod handle of claim 1 wherein the rod blank, the plurality of vibration disks, and the handle member is each constructed
20 of a vibration conductive material.

10. The fishing rod handle of claim 9 wherein the rod blank is constructed of a graphite material.

11. The fishing rod handle of claim 9 wherein the handle member is constructed of a metal material.

5 12. The fishing rod handle of claim 9 wherein each of the plurality of vibration disks is constructed of a metal material.

13. A vibration amplifying fishing rod handle which comprises
a longitudinally extending handle member, said handle member having an external surface and a linear hollow defined within it,
10 said linear hollow being defined by an internal surface,

a longitudinally extending fishing rod blank, a portion of said fishing rod blank being insertable within the linear hollow of said handle member, and

a plurality of vibration members, each said member being
15 attachable to that portion of the fishing rod blank that is inserted within said hollow handle member,

wherein vibrations emanating from the rod blank are transferred through the vibration members and through the handle member to the external surface of the handle member.

14. The fishing rod handle of claim 13 wherein the handle member hollow has a first open end and a second closed end, and including a nose cone, said nose cone having an axially disposed aperture for receiving a portion of the rod blank therewithin and said nose cone
5 being insertable within the first open end of the handle member hollow.

15. The fishing rod handle of claim 13 wherein each vibration member comprises a flat circular disk member having a central aperture for receiving a portion of the rod blank therethrough.

16. The fishing rod handle of claim 15 wherein each vibration
10 member further includes a plurality of prongs extending outwardly from the flat disk member.

17. The fishing rod handle of claim 16 wherein each vibration member has a first disk face and each of the plurality of outwardly extending prongs is bent toward the first disk face.

18. The fishing rod handle of claim 17 wherein the vibration
15 members that are attached to the disk blank are attached such that the prongs of each disk are bent in the same direction.

19. The fishing rod handle of claim 13 wherein the rod blank, the plurality of vibration members, and the handle member is each
20 constructed of a vibration conductive material.

20. The fishing rod handle of claim 19 wherein the rod blank is constructed of a graphite material.

21. The fishing rod handle of claim 19 wherein the handle member is constructed of a metal material.

5 22. The fishing rod handle of claim 19 wherein each of the vibration members is constructed of a metal material.